

Wire transport for aluminium alloys with MIGAL.CO Eco- or Jumbo-Drums



For wire diameters up to 2.4 mm. Without Pneumatic feed assist DLDA1: Sum of the radii of the conduit $\leq 360^\circ$, Length ≤ 5 m • With DLDA1: Sum of the radii $\leq 1.800^\circ$, Length ≤ 50 m

Without DLDA1: Sum of the radii of the conduit $\leq 1.300^\circ$, Length ≤ 25 m • With DLDA1: Sum of the radii $\leq 2.500^\circ$, Length ≤ 75 m

For wire diameters up to 1.6 mm.

Sum of the radii of the conduit $\leq 1.300^\circ$, Length ≤ 25 m

For wire diameters up to 4 mm.

Softliner Conduit
10,40,1,0001

Compression fitting CRNG40
10,10,8,0003

Coupling CRNG40
10,10,8,0002

Plug CRNG40
10,10,8,0001

Maintenance unit for DLDA-1
10,50,1,0002



Rolliner 3G Conduit with Protective hose PA12
10,30,3,0100

Wire inlet Rolliner 3G with retaining clip
10,30,3,0001

Wire inlet Rolliner XL2 with retaining clip
10,20,2,0001

Rolliner XL2 Conduit with Protective hose PA12
10,20,2,0100

Wire outlet Rolliner XL2 with retaining clip
10,20,2,0002

Rolliner 3G Conduit with Protective hose PA12
10,30,3,0100

Wire outlet Rolliner 3G with retaining clip
10,30,3,0002

Softliner Conduit
10,40,1,0001

Compression fitting CRNG40
10,10,8,0003

Plug CRNG40
10,10,8,0001

Coupling CRNG40
10,10,8,0002

Inlet-/Outlet guide 1/2" for DLDA-1
10,50,2,0002

Inlet-/Outlet guide 1/4" for DLDA-1
10,50,2,0001

Insulation plate for DLDA-1
10,50,1,0004

Pneumatic feed assist DLDA-1
10,50,1,0001

Disc ϕ 130 mm *)
10,50,1,0003

Inlet-/Outlet guide 1/4" for DLDA-1
10,50,2,0001

Quick coupling CRNG20
10,30,1,0003

Screw coupling RNG20
10,30,1,0004

Coupling CRNG40
10,10,8,0002

Plug CRNG40
10,10,8,0001

Adapter 1/2" -1/4" with internal thread
10,10,8,0006

Connector CLOOS
19,20,1,0009

Universal connector for wire feeders ASRPR with plastic insert
10,20,1,0012

Screw coupling RNG20
10,30,1,0004

Connector SKS-PF5
10,20,1,0011

Plug CRNG40
10,10,8,0001

Coupling CRNG40
10,10,8,0002

Adapter 1/2" - M20
10,20,1,0014

Option: Wire end control
Sensor with power cable 10,10,7,0001
Wire end sensor block 10,10,7,0005



Pulley ULR-2
10,10,6,0001

Round hood for drums with clamping ring
10,10,2,0001

Square drum hood
10,10,2,0003

Decoiling aid ASH 81
10,10,3,0003

Decoiling aid TOU400/580
10,10,4,0001

Beech wooden balls 40 mm
10,10,3,0002

Universal spreader bar ULT1
10,10,1,0002

Universal drum transport trolley UFTW1
10,10,1,0001

*) When using the Pneumatic feed assist DLDA-1, the discs delivered with the decoiling aid ASH 81 must be replaced by 2 pcs. Disc ϕ 130 mm 10,50,1,0003.

